

Model: MT2100D5

Powered by Mitsubishi

Output Rating

MODEL		Power rating		Voltage available		
		PRIME(1)	STANDBY(2)			
MT2100D5	400V/50HZ	1500KW	1680KW	380/220V	400/230V	415/240V
	PF:0.8	1875KVA	2100KVA			


General Information

Model	MT2100D5		
Engine	S16R-PTA2		
Speed control type	Electronic		
Phase	3		
Control System	Digital		
System voltage	12V/24V		
Frequency	50HZ		
Engine Speed(RPM)	1500		
Fuel Consumption L/hr	Standby power(2)	383	
	Prime Power(1)	355	
	75% prime power	278	
	50% prime power	196	



Dimension and Weight

Dimension	Open	Silent
Length (L)		
Width (W)	NA	NA
Height (H)		
Net Weight		



AGG POWER gensets are compliant with EC mark which include the following directives:

- * 2006/42/EC Machinery safety.
- * 2006/95/EC Low voltage
- * EN 60204-1: 2006+A1:2009, EN ISO 12100:2010, EN ISO 13849-1: 2008, EN 12601: 2010

(1) Prime Power (PRP):

According to ISO 8528-1:2005, Prime power is the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load when operated for an unlimited number of hours per year under the agreed operation conditions with the maintenance intervals and procedures being carried out as prescribed by the manufacturer. The permissible average power output (Ppp) over 24h of operation shall not exceed 70% of the PRP.

(2) Standby Power (ESP):

According to ISO 8528-1:2005, standby power is the maximum power available during a variable electrical power sequence, under the stated operation conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 200h of operation per year with the maintenance intervals and procedures being carried out as prescribed by the manufacturers. The permissible average power output over 24h of operation shall not exceed 70% of the ESP.



-Engine Specification S16R-PTA²

GENERAL ENGINE DATA

Type	4-Cycle, Water Cooled
Aspiration	Turbo-Charged, After Cooler (Jacket water to Cooler)
Cylinder Arrangement	60°V
No. of Cylinders	16
Bore mm(in.)	170 (6.69)
Stroke mm(in.)	180 (7.09)
Displacement liter(ir ³)	65.37 (3989)
Compression Ratio	13.5:1
Dry Weight - Engine only - kg(lb)	6300 (13892)
Wet Weight - Engine only - kg(lb)	6677 (14723)

PERFORMANCE DATA

Steady State Speed Stability Band any Constant Load	
Hydraulic (std.) or Electric Governor - %	±0.25 or better
Maximum Overspeed Capacity - rpm	2100
Moment of inertia of Rotating Components - kg·m ² (lbf·ft ²)	80.83 (1918)
(Includes Std. Flywheel)	
Cyclic Speed Variation with Flywheel a 1800rpm	1/254
1500rpm	1/170

ENGINE MOUNTING

Maximum Bending Moment at Rear Face of Flywheel Housing - kg·m(lbf·ft)	450 (3256)
------------------------------------------------------------------------------	------------

AIR INLET SYSTEM

Maximum Intake Air Restriction (Includes piping)	
With Clean Filter Element - mm H ₂ O (in.H ₂ O)	400 (15.7)
With Dirty Filter Element - mm H ₂ O (in.H ₂ O)	635 (25.0)

EXHAUST SYSTEM

Maximum Allowable Back Pressure - mm H ₂ O (in.H ₂ O)	600 (23.6)
-----------------------------------------------------------------------------------	------------

LUBRICATION SYSTEM

Oil Pressure at Idle - kgf/cm ² (psi)	2 ~ 3 (29 ~ 43)
at Rate Speed - kgf/cm ² (psi)	5 ~ 6.5 (71 ~ 93)
Maximum Oil Temperature - °C(°F)	110 (230)
Oil Capacity of Standard Pan High - liter (U.S.gal)	200 (52.8)
Low - liter (U.S.gal)	140 (37.0)
Total System Capacity (Includes Oil Filter) - liter (U.S.gal)	230 (60.8)
Maximum Angle of Installation (Std. Pan) Front Down	5°
(Engine Only) Front Up	5°
Side to Side	22.5°

COOLING SYSTEM

Coolant Capacity (Engine only) - liter (U.S.gal)	170 (44.9)
Maximum External Friction Head at Engine Outlet - kgf/cm ² (psi)	0.35 (5.0)
Maximum Static Head of Coolant above Crankshaft Center - m(ft)	10 (32.8)
Maximum Outlet Pressure of Engine Water Pump - kgf/cm ² (psi)	2 (28.6)
Standard Thermostat (modulating) Range-°C(°F)	71 ~ 85 (160 ~ 185)
Maximum Coolant Temperature at Engine Outlet-°C(°F)	98 (208)
Minimum Coolant Expansion Space - % of System Capacity	10
Maximum Coolant Temperature at Intercooler Inlet, TK type-°C(°F)	
Maximum Air Restriction on Discharge Side of Radiator and Fan-mm H ₂ O(in.H ₂ O)	10 (0.4)



▪ Alternator

Alternator		
Poles	Num	4
Winding Connections (standard)		Star-serie
Insulation	Class	H class
Enclosure (according IEC-34-5)		IP23
Exciter System		Brushless
Voltage Regulator		A.V.R. (Electronic)
Bearing		Single bearing
Coupling		Flexible disc
Coating type		Standard (Vacuum impregnation)

▪ Options

Engine	Alternator	Generator Sets	Fuel System	Canopy
<ul style="list-style-type: none"> •Water Jacket Preheater •Oil Preheater 	<ul style="list-style-type: none"> •Winding Temperature measuring Instrument •Alternator Preheater •PMG •Anti-damp and anti-corrosion treatment •Anti-condensation heater 	<ul style="list-style-type: none"> •Tools with the machine 	<ul style="list-style-type: none"> • Low fuel level alarm •Automatic fuel feeding system •Fuel T-valves 	<ul style="list-style-type: none"> •Rental Type Canopy •Trailer
Lubricating System	Exhaust System	Cooling System	Control Panel	Voltages
<ul style="list-style-type: none"> •Oil with the machine 	<ul style="list-style-type: none"> •Protection board from hotness 	<ul style="list-style-type: none"> • Front heat protection • Coolant (-30°C) 	<ul style="list-style-type: none"> •Remote control panel • ATS • Remote controller • Synchronizing controller 	<ul style="list-style-type: none"> • 415/240V • 380/220V • 220/127V • 220/127V • 200-115V



Control Panel



Product description

- Single gen-set controller for Stand-by and Prime-power applications
- Direct communication with EFI engines
- Total remote monitoring and control

Key features

- Easy to install, configure and use
- Wide range of communication capabilities including:
 - connection via RS232, RS485, CAN and on board USB
 - internet access using Ethernet or GPRS
 - support for Modbus and SNMP protocols
- Cloud-based monitoring and control
- Active SMS and emails in different languages
- 2x 5 A binary outputs for cranking and fuel solenoid
- Option for up to 16 additional binary inputs/outputs
- Flexible event based history with up to 350 events
- Load shedding, dummy load capability
- Automatic temperature based cooling/heating
- Comprehensive gen-set protections
- Multipurpose flexible timers
- True RMS measurement

Available extension modules

Product	Description	Order code
CM-Ethernet	Ethernet interface	CM2ETHERXBX
CM-GPRS	GSM modem / wireless internet	CM2GPRSXXBX
CM-RS232-485	Dual port interface	CM223248XBX
EM-BIO8-EFCP	8 additional binary inputs/outputs	EM2BIO8EXBX

Functions and protections

Description	ANSI code	Description	ANSI code
Over voltage	59	Load shedding	32P
Under voltage	27	Overload	32
Voltage asymmetry and Phase rotation**	47	Power factor	55
Over frequency	81H	Temperature	49T
Under frequency	81L	Gas (fuel) level	71
Over current*	50 + 51	Earth fault current	50N + 64
Current unbalance	46		

* Short current only

** Fixed setting

